

PRODUCT DATA SHEET



1265 PAPER MASKING TAPE Painter's masking tape.

Product Features:

- * UV resistant for up to 14 days.
- * Resistant to humidity.
- * Creped paper is easily conformable.
- * Excellent resistance to paint and thinners.
- * Easy removal without adhesive residue.
- * Compatible with most common paints and lacquers.

Applications:

- * For wall painting on building and construction sites.
- * Interior masking of windows where adhesive could be exposed to sunlight.
- * Commercial and domestic masking applications.

Product Specifications:

* Adhesive:	Solvent acrylic
* Backing:	Waterproof saturated crepe paper
* Total thickness:	0.125mm
* Colour:	Blue
* Tensile strength:	90N / 25mm.
* Adhesion to steel:	4.8N / 25mm.
* Elongation:	8%.
* Temperature resistance:	80 deg. C
* Maximum width:	1510mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.