

PRODUCT DATA SHEET



135 BLACK PROTECTION TAPE UV Stabilised Polyethylene Tape

Product Features:

- * Adhesive is designed to provide clean removal.
- * High abrasion resistant backing.
- * Highly conformable polyethylene tape.
- * Excellent UV resistance provides superior ageing.
- * Sizes available cut to order.

Applications:

- * Designed especially to protect aluminium and steel frames.
- * Ideal for use during manufacture, transport ation and installation.
- * Used for protecting aluminium window and door frames.
- * Can be used on stainless steel appliances and sheeting.
- * Provides a corrosion protection barrier between dissimilar metals.

Product Specifications:

* Adhesive:	Rubber resin
* Backing:	Polyethylene
* Total thickness:	0.108mm
* Colour:	Black
* Tensile strength:	33N/25mm
* Adhesion:	1.4N/25mm
* UV Resistance:	Excellent
* Elongation:	450%
* Max width:	1350mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.