

# PRODUCT DATA SHEET



## 160 ELECTRICAL TAPE Single Sided Reinforced Polyester

### Product Features & Applications:

- \* Heavy duty usage in air and oil filled transformers.
- \* Slot edging of Nomex\* (Nomex\* is a Dupont registered trademark).
- \* Lead and saddle tie-down.
- \* Reinforcements.
- \* Holding and separating ground insulation.
- \* Bundling motor coils and coil covering.
- \* Economical glass cloth replacement (class 155 deg. C).

### Product Specifications:

* Temperature:	155 deg. C
* Backing:	Glass reinforced polyester
* Adhesive:	Acrylic thermosetting
* Colour:	Cream
* Backing thickness:	0.165mm
* Total thickness:	0.203mm
* Tensile:	612.5 N/10mm
* Elongation:	6%
* Adhesion to steel:	4.95N/10mm
* Insulation resistance:	10 <sup>4</sup> megohms
* Direct electrolytic corrosion:	1
* Dielectric strength:	6500 volts
* Moisture resistance:	Excellent
* Solvent resistance:	Excellent
* Storage stability:	Excellent
* Max width:	1300mm

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.