

PRODUCT DATA SHEET



7300 SERIES GLAZING TAPE Double Sided Adhesive Coated PVC Foam.

Product Features and Applications:

- * Double sided high tack acrylic adhesive.
- * Designed for use in commercial and residential glazing systems.
- * The closed cell structure completely seals out air, moisture and dust.
- * Provides a watertight seal when compressed 30% or more..
- * Ideal for marine window glazing applications.
- * Low thermal conductivity reduces heat transfer.
- * Excellent resistance to aging.

Product Specifications:

* Adhesive:	Acrylic
* Foam:	Closed cell PVC foam
* Thicknesses:	1.5, 3.0, 5.0mm
* Colours:	Black
* Liner:	Blue PE
* Tensile strength:	0.35 Mps min.
* Density:	220-300 kg/m ³
* Force to compress at 30%:	168N/CM ² - 6mm
* Compression set:	10% max
* Hardness:	55-75 (shore 00)
* Elongation:	150% min
* Watertight seal at:	20% compression
* Water absorption:	8% by volume
* Thermal conductivity:	0.16 kcal
* Temperature resistance:	-50° to 60° C.
* Maximum width:	Up to 1250mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.