

PRODUCT DATA SHEET



800 SERIES FOAM SEALING TAPE Single Sided Medium Soft PVC - Black

Product Features:

- * Easy to compress.
- * Highly conformable.
- * Ideal for sealing tight radial curves.
- * Cushions and absorbs shock.
- * Specially formulated to meet automotive industry specifications.
- * Clean cutting and smooth fastener penetration.
- * Moisture and dust seal at 30% compression.
- * Laminated with a long life acrylic adhesive.

Product Specifications:

- | | |
|---------------------------|-----------------------|
| * Thickness: | 1.6 to 19mm |
| * Density: | 112kg per cubic metre |
| * Hardness: | 14 (Shore 00) |
| * Colour: | Black |
| * Tensile strength: | 173kPa |
| * Force to compress 25%: | 15kPa |
| * Water absorption: | 1.1% by volume |
| * Temperature resistance: | -40 to 80 deg. C |
| * Fungi resistance: | Excellent |
| * Oxidation resistance: | Excellent |
| * Weather resistance: | Excellent |
| * Elongation: | 150% |

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.

PRODUCT DATA SHEET



800 SERIES FOAM SEALING TAPE Single Sided Medium Soft PVC - Grey

Product Features:

- * Easy to compress.
- * Highly conformable.
- * Ideal for sealing tight radial curves.
- * Cushions and absorbs shock.
- * Clean cutting and smooth fastener penetration.
- * Moisture and dust seal at 30% compression.
- * Laminated with a long life acrylic adhesive.

Product Specifications:

* Thickness:	3.2 to and 12.7mm
* Density:	128kg per cubic metre
* Hardness:	25 (Shore 00)
* Colour:	Grey
* Tensile strength:	207kPa
* Force to compress 25%:	24kPa
* Water absorption:	1.0% by volume
* Temperature resistance:	-40 to 80 deg. C
* Fungi resistance:	Excellent
* Oxidation resistance:	Excellent
* Weather resistance:	Excellent
* Elongation:	150%

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.