

PRODUCT DATA SHEET



824 STRAPPING TAPE Single Sided Polypropylene

Product Features:

- * High tensile strength backing.
- * Excellent UV resistance.
- * Good adhesion and humidity resistance.
- * Good chemical and moisture resistance.
- * Suits hand, desk and bench dispensers.

Applications:

- * General purpose palletising.
- * Packaging and wrapping.
- * Strapping and bundling.

Product Specifications:

- | | |
|---------------------------|--------------------------|
| * Adhesive: | Rubber |
| * Backing: | Tensilised polypropylene |
| * Backing thickness: | 0.075mm |
| * Total thickness: | 0.098mm |
| * Colours: | Black |
| * Tensile strength: | 600N per 25mm |
| * Adhesion to steel: | 15N per 25mm |
| * Temperature resistance: | -40 to 60 deg C. |
| * Elongation: | 8% |

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.