

PRODUCT DATA SHEET



A8080G ACRIBOND TAPE Double Sided Acrylic Foam

Product Features:

- * Superior adhesion performance.
- * Excellent durability and conformability.
- * Convenient and easy to use.
- * Economical.

Applications:

- * Replace rivets, spot welds, and liquid adhesives.
- * Body side mouldings, bumper mouldings and emblems.
- * Auto side visors and weather strips.
- * Interior and exterior mounting.



Product Specifications:

* Adhesive:	Acrylic
* Carrier:	Acrylic foam
* Colour:	Dark Grey
* Thickness:	0.80mm +/- 50um
* Liner:	Green PE
* Density:	800kg per cu. m. +/- 100kg
* Tensile strength:	7,000gf per cm ² .
* Dynamic shear strength:	7,000gf per cm ² . (after 24 hours)
* Peel strength:	4,000gf per 25mm (180 deg.)
* Temperature resistance:	160° C (short term) 100° C (long term)
* Maximum width:	800mm
* Roll length:	66m

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.