

# PRODUCT DATA SHEET



## A8150G ACRIBOND TAPE Double Sided Acrylic Foam

### Product Features:

- \* Superior adhesion performance.
- \* Excellent durability and conformability.
- \* Convenient and easy to use.
- \* Economical.

### Applications:

- \* Replace rivets, spot welds, and liquid adhesives.
- \* Body side mouldings, bumper mouldings and emblems.
- \* Auto side visors and weather strips.
- \* Interior and exterior mounting.



### Product Specifications:

* Adhesive:	Acrylic
* Carrier:	Acrylic foam
* Colour:	Dark Grey
* Thickness:	1.5mm +/- 50um
* Liner:	Green PE
* Density:	800kg per cu. m. +/- 100kg
* Tensile strength:	6,000gf per cm <sup>2</sup> .
* Dynamic shear strength:	6,000gf per cm <sup>2</sup> . (after 24 hours)
* Peel strength:	4,500gf per 25mm (180 deg.)
* Temperature resistance:	160° C (short term) 100° C (long term)
* Maximum width:	800mm
* Roll length:	30m

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.