

# PRODUCT DATA SHEET



## 138 FLASHING TAPE

### Single Sided Reinforced Aluminium Foil

#### Product Features:

- \* Reinforced aluminium foil laminated with butyl adhesive.
- \* Extremely high initial tack.
- \* Excellent adhesion.
- \* Exterior grade weatherproof tape.
- \* Very good UV and moisture tolerance.
- \* Bonds to most clean surfaces.
- \* Sizes available cut to order.

#### Applications:

- \* Designed for waterproofing and sealing.
- \* Ideal for roof repairs, guttering, downpipes.
- \* Seal around skylights and plumbing.

#### Product Specifications:

- |                           |                  |
|---------------------------|------------------|
| * Backing                 | Aluminium foil   |
| * Adhesive:               | Butyl rubber     |
| * Carrier:                | Rayon cloth      |
| * Total thickness:        | 1.15mm           |
| * Colour:                 | Silver           |
| * Peel 180 deg:           | 19.6 N per 25mm  |
| * Temperature resistance: | -20 to 65 deg C. |
| * Liner:                  | Brown paper      |
| * Maximum width:          | 1100mm           |

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.