

PRODUCT DATA SHEET



300 SERIES FOAM SEALING TAPE Single Sided Closed Cell Polyethelene.

Product Features:

- * Cushions and absorbs shock.
- * Acrylic adhesive for permanent mounting.
- * Good noise suppression properties.
- * Good thermal stability.

Applications:

- * Sealing air conditioning joints.
- * Weatherseal strip around door and window frames.
- * Used in concrete formwork.
- * Air and or oil filtration.

Product Specifications:

- * Thickness: 3mm, 5mm and 10mm
- * Density: 33kg per cubic metre
- * Colour: Charcoal
- * Tensile strength: 4.4kg per sq cm
- * Tear resistance: 2.4kg per cm
- * Adhesion to steel: 6.60 N per cm
- * Temperature resistance: -10 to 100 deg. C
- * Compression set: 23% @ 50% deflection
- * Elongation: 250%
- * Maximum width: 1200mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.