

# PRODUCT DATA SHEET



## 5410 DOUBLE SIDED FOAM TAPE Double coated PE Foam Tape.

### Product Features:

- \* High tack adhesive has good adhesion to a wide variety of surfaces.
- \* Good quick stick makes application easy.
- \* Flexible foam conforms to contoured surfaces.
- \* Closed cell, cross linked foam does not absorb water.
- \* Foam provides good thermal insulation properties.
- \* High shear strength for secure bonding.
- \* Good UV, weathering and chemical resistance.

### Applications:

- \* Mounting and joining nameplates, plastic parts, signs and emblems.
- \* Permanent fixing of house wares, kitchen and bathroom accessories.
- \* Suitable for permanent fixing of glass and mirrors.

### Product Specifications:

- |                            |                            |
|----------------------------|----------------------------|
| * Carrier:                 | Closed cell PE Foam        |
| * Liner:                   | White bi-siliconised paper |
| * Adhesive:                | Acrylic (Solvent based)    |
| * Total thickness:         | 1.1mm                      |
| * Colour:                  | White                      |
| * Adhesion to steel:       | >22.5N per 25mm            |
| * Normal tensile strength: | >31N per 25mm              |
| * Temperature resistance:  | -40 to 120 deg C.          |
| * Elongation:              | 150%                       |
| * Maximum width:           | 1500mm                     |

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.