

PRODUCT DATA SHEET



5416 DOUBLE SIDED FOAM TAPE Double coated PE Foam Tape.

Product Features:

- * High tack adhesive has good adhesion to a wide variety of surfaces.
- * Good quick stick makes application easy.
- * Flexible foam conforms to contoured surfaces.
- * Closed cell, cross linked foam does not absorb water.
- * Foam provides good thermal insulation properties.
- * High shear strength for secure bonding.
- * Good UV, weathering and chemical resistance.

Applications:

- * Mounting and joining nameplates, plastic parts, signs and emblems.
- * Permanent fixing of house wares, kitchen and bathroom accessories.
- * Suitable for permanent fixing of glass and mirrors.
- * Very good for exterior applications.

Product Specifications:

- | | |
|----------------------------|----------------------------|
| * Carrier: | Cross-linked PE Foam |
| * Liner: | White bi-siliconised paper |
| * Adhesive: | Acrylic (Solvent based) |
| * Total thickness: | 1.6mm |
| * Colour: | White |
| * Adhesion to steel: | >17.5N per 25mm |
| * Normal tensile strength: | 20N per 25mm |
| * Temperature resistance: | -30 to 90 deg C. |
| * Elongation: | 150% |
| * Maximum width: | 1500mm |

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.