

PRODUCT DATA SHEET



5432 DOUBLE SIDED FOAM TAPE Double coated PE Foam Tape.

Product Features:

- * High tack adhesive has good adhesion to a wide variety of surfaces.
- * Good quick stick makes application easy.
- * Flexible foam conforms to contoured surfaces.
- * Closed cell, cross linked foam does not absorb water.
- * Foam provides good thermal insulation properties.
- * High shear strength for secure bonding.

Applications:

- * Mounting and joining nameplates, plastic parts, signs and emblems.
- * Permanent fixing of house wares, kitchen and bathroom accessories.

Product Specifications:

- | | |
|----------------------------|-------------------------|
| * Carrier: | Cross-linked PE Foam |
| * Liner: | White Glassine Paper |
| * Adhesive: | Acrylic (Solvent based) |
| * Total thickness: | 3.0mm |
| * Colour: | White |
| * Peel adhesion: | 2.5kg per 25mm |
| * Normal tensile strength: | 15kg per 25mm sq. |
| * Temperature resistance: | -20 to 80 deg C. |
| * Maximum width: | 1250mm |

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.