

# PRODUCT DATA SHEET



## 1260 PAPER MASKING TAPE Painter's masking tape.

### Product Features:

- \* Highly resistant to moisture and water.
- \* Creped paper is easily conformable.
- \* Excellent resistance to paint and thinners.
- \* Easy removal without adhesive residue, up to 7 days.
- \* Compatible with most common paints and lacquers.

### Applications:

- \* Ideal for automotive applications.
- \* Building and construction sites.
- \* Commercial and domestic masking applications.

### Product Specifications:

- |                           |                                  |
|---------------------------|----------------------------------|
| * Adhesive:               | Natural rubber                   |
| * Backing:                | Waterproof saturated crepe paper |
| * Total thickness:        | 0.130mm                          |
| * Colour:                 | Yellow                           |
| * Tensile strength:       | 87.5N / 25mm.                    |
| * Adhesion to steel:      | 4.8N / 25mm.                     |
| * Elongation:             | 8%.                              |
| * Temperature resistance: | 80 deg. C (30 mins).             |
| * Maximum width:          | 1510mm                           |

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.