

PRODUCT DATA SHEET



130 ALL WEATHER TAPE UV Stabilised Polyethylene Film

Product Features:

- * Aggressive adhesive to polyethylene, PVC and other surfaces.
- * Clear film doesn't spoil your product's appearance.
- * Long ageing acrylic adhesive.

Applications:

- * Suitable for joining and repairing polyethylene sheeting.
- * General purpose exterior joining and repairs.
- * Repair or reinforce greenhouses and tunnel houses.
- * Used as an overwrap on piping and electrical binding.
- * Antishatter and surface protection.
- * Waterproofing and sealing.

Product Specifications:

* Adhesive:	Solvent based acrylic
* Backing:	Polyethylene
* Backing thickness:	0.100mm
* Total thickness:	0.135mm
* Colour:	Transparent
* Tensile strength:	55N per 25mm
* Adhesion to steel:	10N per 25mm
* Temperature resistance:	80 deg. C.
* UV resistance:	Excellent
* Elongation:	450%

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.