

PRODUCT DATA SHEET



131 HOUSE WRAP TAPE

UV Stabilised Woven Polyethylene Film

Product Features:

- * Strong adhesion to woven and spunbound membranes.
- * Excellent UV protection.
- * Exhibits excellent properties for aging and weathering.
- * Air and waterproof seal.
- * Hand tearable, easy to use, saves time.
- * No liner to remove, saves time and money and waste.

Applications:

- * Suitable for sealing and repairing house wrap membranes.
- * Sealing around windows and doors.
- * General purpose exterior joining and repairs.
- * Repair or reinforce greenhouses and tunnel houses.
- * Maintain and repair agricultural films.
- * Waterproofing and sealing.

Product Specifications:

| | |
|---------------------------|----------------------------------|
| * Adhesive: | Solvent based acrylic |
| * Backing: | Polyethylene, polyethylene cloth |
| * Total thickness: | 0.170mm |
| * Colour: | White |
| * Tensile strength: | 48N per 10mm |
| * Adhesion to steel: | 7N per 10mm |
| * Temperature resistance: | 90 deg. C. |
| * UV resistance: | Excellent |
| * Elongation: | 9% |

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.