

# PRODUCT DATA SHEET



## 135 BLACK PROTECTION TAPE UV Stabilised Polyethylene Tape

### Product Features:

- \* Adhesive is designed to provide clean removal.
- \* High abrasion resistant backing.
- \* Highly conformable polyethylene tape.
- \* Excellent UV resistance provides superior ageing.
- \* Sizes available cut to order.

### Applications:

- \* Designed especially to protect aluminium and steel frames.
- \* Ideal for use during manufacture, transport ation and installation.
- \* Used for protecting aluminium window and door frames.
- \* Can be used on stainless steel appliances and sheeting.
- \* Provides a corrosion protection barrier between dissimilar metals.

### Product Specifications:

* Adhesive:	Rubber resin
* Backing:	Polyethylene
* Total thickness:	0.108mm
* Colour:	Black
* Tensile strength:	33N/25mm
* Adhesion:	1.4N/25mm
* UV Resistance:	Excellent
* Elongation:	450%
* Max width:	1350mm

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.