

# PRODUCT DATA SHEET



## 300 SERIES FOAM SEALING TAPE Single Sided Closed Cell Polyethelene.

### Product Features:

- \* Cushions and absorbs shock.
- \* Acrylic adhesive for permanent mounting.
- \* Good noise suppression properties.
- \* Good thermal stability.

### Applications:

- \* Sealing air conditioning joints.
- \* Weatherseal strip around door and window frames.
- \* Used in concrete formwork.
- \* Air and or oil filtration.

### Product Specifications:

- \* Thickness: 3mm, 5mm and 10mm
- \* Density: 33kg per cubic metre
- \* Colour: Charcoal
- \* Tensile strength: 4.4kg per sq cm
- \* Tear resistance: 2.4kg per cm
- \* Adhesion to steel: 6.60 N per cm
- \* Temperature resistance: -10 to 100 deg. C
- \* Compression set: 23% @ 50% deflection
- \* Elongation: 250%
- \* Maximum width: 1200mm

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.