

# PRODUCT DATA SHEET



## 800 SERIES FOAM SEALING TAPE Single Sided Medium Soft PVC - Black

### Product Features:

- \* Easy to compress.
- \* Highly conformable.
- \* Ideal for sealing tight radial curves.
- \* Cushions and absorbs shock.
- \* Specially formulated to meet automotive industry specifications.
- \* Clean cutting and smooth fastener penetration.
- \* Moisture and dust seal at 30% compression.
- \* Laminated with a long life acrylic adhesive.

### Product Specifications:

* Thickness:	1.6 to 19mm
* Density:	112kg per cubic metre
* Hardness:	14 (Shore 00)
* Colour:	Black
* Tensile strength:	173kPa
* Force to compress 25%:	15kPa
* Water absorption:	1.1% by volume
* Temperature resistance:	-40 to 80 deg. C
* Fungi resistance:	Excellent
* Oxidation resistance:	Excellent
* Weather resistance:	Excellent
* Elongation:	150%

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.

# PRODUCT DATA SHEET



## 800 SERIES FOAM SEALING TAPE Single Sided Medium Soft PVC - Grey

### Product Features:

- \* Easy to compress.
- \* Highly conformable.
- \* Ideal for sealing tight radial curves.
- \* Cushions and absorbs shock.
- \* Clean cutting and smooth fastener penetration.
- \* Moisture and dust seal at 30% compression.
- \* Laminated with a long life acrylic adhesive.

### Product Specifications:

* Thickness:	3.2 to and 12.7mm
* Density:	128kg per cubic metre
* Hardness:	25 (Shore 00)
* Colour:	Grey
* Tensile strength:	207kPa
* Force to compress 25%:	24kPa
* Water absorption:	1.0% by volume
* Temperature resistance:	-40 to 80 deg. C
* Fungi resistance:	Excellent
* Oxidation resistance:	Excellent
* Weather resistance:	Excellent
* Elongation:	150%

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.