

# PRODUCT DATA SHEET



## 824 STRAPPING TAPE Single Sided Polypropylene

### Product Features:

- \* High tensile strength backing.
- \* Excellent UV resistance.
- \* Good adhesion and humidity resistance.
- \* Good chemical and moisture resistance.
- \* Suits hand, desk and bench dispensers.

### Applications:

- \* General purpose palletising.
- \* Packaging and wrapping.
- \* Strapping and bundling.

### Product Specifications:

- \* Adhesive: Rubber
- \* Backing: Tensilised polypropylene
- \* Backing thickness: 0.075mm
- \* Total thickness: 0.098mm
- \* Colours: Black
- \* Tensile strength: 600N per 25mm
- \* Adhesion to steel: 15N per 25mm
- \* Temperature resistance: -40 to 60 deg C.
- \* Elongation: 8%

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.