

# PRODUCT DATA SHEET



## 826 BI-DIRECTIONAL FILAMENT TAPE Single Sided Polypropylene

### Product Features:

- \* High cross direction tensile strength backing.
- \* Aggressive shear resistant adhesive.
- \* Strong fibreglass reinforced filaments.
- \* Excellent adhesion for cold weather and humidity resistance.
- \* Good chemical and moisture resistance.

### Applications:

- \* Heavy duty palletising.
- \* Packaging and wrapping.
- \* Strapping and bundling.

### Product Specifications:

- |                           |  |
|---------------------------|--|
| * Adhesive:               | Rubber resin                                       |
| * Backing:                | Polypropylene with cross link fibreglass filaments |
| * Backing thickness:      | 0.10mm   |
| * Total thickness:        | 0.13mm   |
| * Colours:                | Cream  |
| * Tensile strength:       | 575N per 25mm                                      |
| * Adhesion to steel:      | 25N per 25mm                                       |
| * Temperature resistance: | 60 deg C.  |
| * Elongation:             | 6%   |

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.