

PRODUCT DATA SHEET



UHMW

Ultra High Molecular Weight Polyethylene Film.

Product Features:

- * Clear abrasion resistant polyethylene film.
- * High tack acrylic pressure sensitive adhesive.
- * Good quick stick makes application easy.
- * Polyethylene film provides a 'slippery surface'.
- * Provides a low coefficient of friction to reduce wear.

Applications:

- * Guide rails and chute linings.
- * Sliding doors and drawers.
- * Sewing and assembly tables.
- * Allows product to slide easier.

Product Specifications:

* Backing:	UHMW Polyethylene
* Adhesive:	Acrylic
* Total thickness:	0.177mm
* Liner:	Blue PE
* Colour:	Translucent
* Tensile strength:	50N/50mm
* Adhesion to steel:	700gf/25mm 180deg peel
* Temperature resistance:	66 deg C.
* Elongation:	300%
* Maximum width:	580mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.